



Studio T12



Technical Specifications

Models

L0.82120.B	STUDIO T12 MAN, blue/silver, 220 - 250 V AC, bare ends incl. 4-leaf barndoor
------------	---

Accessories

L2.82150.0	4-leaf barndoor (510 mm / 20.1")
L2.82155.0	Filter Frame (495 mm / 19.5")
L2.82160.0	Set of 4 scrims (495 mm / 19.5")
L2.82160.A	Scrim, full single (495 mm / 19.5")
L2.82160.B	Scrim, full double (495 mm / 19.5")
L2.82160.C	Scrim, half single (495 mm / 19.5")
L2.82160.D	Scrim, half double (495 mm / 19.5")
L2.89063.0	Speed ring circular (9435)
L2.89059.0	Chimera Lightbank Daylite Plus "L", incl. 3 front screens (8645)
L2.8800561	Wind-up Stand LS.6 (083NWA)
L2.76959.0	Wheel set with brakes, Ø 75 mm / M10 mount with brakes (104)
L2.88706.0	Wheel set with brakes, Ø 125 mm / M10 mount with brakes (251)
L2.88096.0	Wheel set with brakes, Ø 160 mm / M10 mount with brakes (374)
L2.76989.0	ARRI Swivelling C Clamp (C150)
L2.80866.0	Safety cable (6 mm) 1 m, with "Kettbiner"
L2.0000885	T12 Top latch for heavy accessories

Lamps

BSR100-32M (KOTO)

BSR120-32M (KOTO)



BSE100-32M/200V (KOTO)

BSE120-32M/200V (KOTO)

Technical Data

Lamphead Type:	Fresnel, 12000 W
Reflector Type:	Spherical specular high purity aluminum
Lamp Type:	12000 W / 230 V monoplane; CP83 10000 W / 230 V monoplane
Power Consumption:	12000 W, 10000 W
Voltage Range:	230 V
Lamp Base:	G38
Dimmability:	Yes, 0 to 100 % via external dimming system
Cable Options:	bare ends
Correlated Color Temperature:	3,200 K
Beam Angle:	13° to 63°
Product Weight:	26,5 kg / 58.4 lbs
Shipping Weight:	46 kg / 101.5 lbs (incl. pallet)
Product Size (H x W x L):	748 x 682 x 562 mm / 29.45 x 26.85 x 22.13"
Shipping Size (H x W x L):	695 x 725 x 780 mm / 27.36 x 28.54 x 30.71"
Lens Diameter:	420 mm / 16.54"
Accessory Diameter:	495 mm / 19.49" (Scrim)
Barndoor:	510 mm / 20.08"
Mounting:	Spigot 28 mm / 1 1/8" (1.1")
Protection Class / IP Rating:	I / IP20
Certifications:	CE, CB, GS, cNRTLus

Studio T24



Technical Specifications

Models

L1.82270.B	STUDIO T24 MAN, blue/silver, 220 - 250 V AC, International Connector
L0.82270.D	STUDIO T24 Set MAN, blue/silver, 220 - 250 V AC, International Connector incl. barndoor, ADM 24 dimmer, mains cable, head to dimmer cable 15 m

Accessories

L2.71100.0	4-leaf barndoor (740 mm / 29.1")
L2.71110.0	Filter Frame (740 mm / 29.1")
L2.71115.0	Set of 4 scrims (740 mm / 29.1")
L2.71115.A	Scrim, full single (740 mm / 29.1")
L2.71115.B	Scrim, full double (740 mm / 29.1")
L2.71115.C	Scrim, half single (740 mm / 29.1")
L2.71115.D	Scrim, half double (740 mm / 29.1")
L2.89064.0	Speed ring circular (9464)
L2.82765.0	Retrofit lampcarriage with fan for STUDIO T24 (220/230 V~ version)
L2.83396.0	Retrofit lampcarriage with fan for STUDIO T24 (200 V~ version)
L2.82294.0	Head-to-Ballast/Dimmer cable 12/18/24 kW, 15 m, International connector (VEAM)
L2.82294.A	Head-to-Ballast/Dimmer cable 12/18/24 kW, 20 m, International connector (VEAM)
L2.82297.0	Mains cable 125 A / 230 V, 7 m, International connector (Cannon) / CEE blue
L2.82296.0	Dimmer ADM 24, 24 kW / 230 V, with lamp hour counter, XLR-5 pin connector for remote control, pre-heat function, international connector, blue standard housing with handle
L2.80866.0	Safety cable (6 mm) 1 m, with "Kettbiner"
L2.89218.0	Lamp T 20000 W / 230 V G38 CP/99 (Osram)
L2.89219.K	Lamp T 24000 W / 240 V G38 (GE)

Lamps

BSE200-32M/200V (KOTO)

BSE240-32M/200V (KOTO)

Technical Data

Lamphead Type:	Fresnel, 24000 W
Reflector Type:	Spherical specular high purity aluminum
Lamp Type:	24000 W monoplane; CP99 20000 W monoplane, 230 V
Power Consumption:	24000 W, 20000 W
Voltage Range:	230 V
Lamp Base:	G38
Dimmability:	Yes, 0 to 100 % via external dimming system
Cable Options:	International Connector
Correlated Color Temperature:	3,200 K
Beam Angle:	14° to 55°
Product Weight:	60.6 kg / 133.6 lbs
Shipping Weight:	114 kg / 251.3 lbs (incl. pallet)
Product Size (H x W x L):	1068 x 1040 x 830 mm / 42.1 x 40.9 x 32.7"
Shipping Size (H x W x L):	1135 x 1050 x 1170 mm / 44.7 x 41.3 x 46.1"
Lens Diameter:	625 mm / 24.61"
Accessory Diameter:	740 mm / 29.13" (Scrim)
Barndoor:	740 mm / 29.13"
Mounting:	Spigot 28 mm / 1 1/8" (1.1")
Protection Class / IP Rating:	I / IP20
Certifications:	CE, CB, GS, cNRTLus