



品名	定格 電圧 [V]	ランプ 電力 [W]	色温度 [K]	全光束 [Lm]	定格 寿命 [hr]	外観寸法 (mm)			概略図	フィラメント タイプ	口金	補足
						A(管径)	B(全長)	C(光中心)				
JCD100V200WC	100	200	3200	5000	75	20	62	36.5	Fig-1	CC-6	G5.3	
JCD100V300WCC	100	300	3200	7500	150	22	62	36.5	Fig-1	CC-6	GY9.5	
JCD100V300WCL	100	300	3200	7500	150	16	50	25.5	Fig-1	CC-6	G6.35 /15*19	
JCD100V300WT	100	300	3050	6600	500	16	50	25.5	Fig-2	CC-6	G6.35	
JCD100V500WCC	100	500	3200	12500	150	22	62	36.5	Fig-1	CC-6	GY9.5	
JCD100V500WCL	100	500	3200	12500	150	22	62	37	Fig-1	CC-6	G6.35 /15*19	
JCD120V650WL	120	650	3200	16200	150	22	62	37	Fig-1	CC-6	G6.35	
JCD240/250V650WC	240	650	3200	16200	50	22	62	37	Fig-1	2 CC-8	GY9.5	
JCD240/250V650WL	240	650	3200	16500	50	24	62	36.5	Fig-1	2 CC-8	G6.35 /15*19	

品名	定格 電圧 [V]	ランプ 電力 [W]	色温度 [K]	全光束 [Lm]	定格 寿命 [hr]	外観寸法 (mm)			概略図	フィラメント タイプ	口金	補足
						A(管径)	B(全長)	C(光中心)				
DVY120V650W	120	650	3200	16200	75	22	62	37	Fig-1	CC-6	G5.3	

概略図




Fig-1




Fig-2

口金図



G5.3



GY9.5



G6.35



G6.35/15*19