



Compact 2500 Theatre



Technical Specifications

Models

L1.73680.B	ARRI COMPACT 2500 Theatre (MAN, grey, VEAM) incl. theatre cassette
L1.73680.F	ARRI COMPACT 2500 Theatre (MAN, grey, Schaltbau GTV standard) incl. theatre cassette
L1.73690.B	ARRI COMPACT 2500 Theatre (MOT*, grey, VEAM) incl. theatre cassette
L1.73690.F	ARRI COMPACT 2500 Theatre (MOT*, grey, Schaltbau GTV standard) incl. theatre cassette



Accessories

L2.76640.0	EB 2.5/4, ALF, 50/60/75 Hz, International (VEAM), 230 V~, bare ends
L2.76641.0	EB 2.5/4, ALF, DMX, 50/60/75 Hz, International (VEAM), 230 V~, bare ends
L2.76650.0	EB 2.5/4, ALF, CCL, 50/60/75 Hz, International (VEAM), 230 V~, bare ends
L2.76646.0	EB 2.5/4, DMX, 50/60/75 Hz, International (VEAM), 120/230 V~, bare ends
L2.75620.0	Head-to-Ballast cable 2500/4000 W, 7 m, International connector (VEAM)
L2.75620.F	Head-to-Ballast cable 2500/4000 W, 7 m, Schaltbau
L2.75620.C	Head-to-Ballast cable 2500/4000 W, 15 m, International connector (VEAM)
L2.75620.E	Head-to-Ballast cable 2500/4000 W, 15 m, Schaltbau
L2.40950.0	4-leaf barndoor, TRUE BLUE (344 mm / 13.5")
L2.40960.0	8-leaf barndoor, TRUE BLUE (344 mm / 13.5")
L2.80970.0	Filter Frame (330 mm / 13.0")
L2.80975.0	Snoot (344 mm / 13.5") with variable aperture
L2.80866.0	Safety cable (6 mm) 1 m, with "Kettbiner"
L2.0003883	Lamp DIS 2500 W/SE G38 UV-B (Koto)

Technical Data

Lamphead Type:	Fresnel, 2500 W
Reflector Type:	Spherical specular high purity aluminum
Lamp Type:	Metal Halide 2500 W/SE
Power Consumption:	2500 W
Voltage Range:	115 V
Lamp Base:	G38
Dimmability:	Yes, 50 to 100 % via ARRI Ballast Unit
Cable Options:	VEAM, Schaltbau (GTV standard)
Correlated Color Temperature:	6,000 K
Beam Angle:	7° to 59°
Product Weight:	approx. 23 kg / 51 lbs
Shipping Weight:	approx. 27 kg / 60 lbs
Product Size (H x W x L):	770 x 590 x 396 mm / 30.3 x 23.2 x 15.6"
Shipping Size (H x W x L):	670 x 610 x 620 mm / 26.4 x 24 x 24.4"
Lens Diameter:	250 mm / 9.8"
Accessory Diameter:	330 mm / 13" (Filter Insertion)
Barndoor:	344 mm / 13.5"
Mounting:	Spigot 28 mm / 1 1/8" (1.1")
Protection Class / IP Rating:	I / IP23
Certifications:	CE, CB, GS, cNRTLus

Compact 4000 Theatre



Technical Specifications

Models

L1.74010.B	ARRI COMPACT 4000 Theatre (MAN, grey, VEAM) incl. theatre cassette
L1.74010.F	ARRI COMPACT 4000 Theatre (MAN, grey, Schaltbau GTV standard) incl. theatre cassette
L1.74020.B	ARRI COMPACT 4000 Theatre (MOT*, grey, VEAM) incl. theatre cassette
L1.74020.F	ARRI COMPACT 4000 Theatre (MOT*, grey, Schaltbau GTV standard) incl. theatre cassette

Accessories

L2.76640.0	EB 2.5/4, ALF, 50/60/75 Hz, International (VEAM), 230 V~, bare ends
L2.76641.0	EB 2.5/4, ALF, DMX, 50/60/75 Hz, International (VEAM), 230 V~, bare ends
L2.76650.0	EB 2.5/4, ALF, CCL, 50/60/75 Hz, International (VEAM), 230 V~, bare ends
L2.76646.0	EB 2.5/4, DMX, 50/60/75 Hz, International (VEAM), 120/230 V~, bare ends
L2.75620.0	Head-to-Ballast cable 2500/4000 W, 7 m, International connector (VEAM)
L2.75620.F	Head-to-Ballast cable 2500/4000 W, 7 m, Schaltbau
L2.75620.C	Head-to-Ballast cable 2500/4000 W, 15 m, International connector (VEAM)
L2.75620.E	Head-to-Ballast cable 2500/4000 W, 15 m, Schaltbau
L2.41200.0	4-leaf barndoor, TRUE BLUE (413 mm / 16.3")
L2.81210.0	8-leaf barndoor (413 mm / 16.3")
L2.81220.0	Filter Frame (400 mm / 15.8")
L2.81225.0	Snoot (413 mm / 16.3") with variable aperture
L2.79946.0	IR protective glass (400 mm) between lamphead and shutter
L2.80866.0	Safety cable (6 mm) 1 m, with "Kettbiner"
L2.0003882	Lamp DIS 4000 W/SE G38 UV-B (Koto)

Technical Data

Lamphead Type:	Fresnel, 4000 W
Reflector Type:	Spherical specular high purity aluminum
Lamp Type:	Metal Halide 4000 W/SE
Power Consumption:	4000 W
Voltage Range:	200 V
Lamp Base:	G38
Dimmability:	Yes, 50 to 100 % via ARRI Ballast Unit
Cable Options:	VEAM, Schaltbau (GTV standard)
Correlated Color Temperature:	6,000 K
Beam Angle:	7° to 65°
Product Weight:	approx. 27 kg / 60 lbs
Shipping Weight:	approx. 37 kg / 82 lbs
Product Size (H x W x L):	856 x 656 x 456 mm / 33.7 x 25.8 x 18"
Shipping Size (H x W x L):	695 x 725 x 775 mm / 27.4 x 28.5 30.5"
Lens Diameter:	300 mm / 11.8"
Accessory Diameter:	400 mm / 15.8" (Filter Insertion)
Barndoor:	413 mm / 16.3"
Mounting:	Spigot 28 mm / 1 1/8" (1.1")
Protection Class / IP Rating:	I / IP23
Certifications:	CE, CB, GS, cNRTLus